

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number
WO 2005/062986 A2

(51) International Patent Classification: Not classified

(21) International Application Number:
PCT/US2004/043742

(22) International Filing Date:
23 December 2004 (23.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/533,570 31 December 2003 (31.12.2003) US

(71) Applicant (for all designated States except US): THE
UNIVERSITY OF SOUTH CAROLINA [US/US]; 109
Osborne Administration, Columbia, South Carolina 29208
(US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MYRICK, Michael
L. [US/US]; 5 Castlevale Circle, Irmo, South Carolina

29063 (US). MINEY, Paul G. [IE/IE]; AMORSET
MANORHAMILTON, CO. LEITRIM Ireland (IE).
SCHIZA, Maria V. [GR/US]; 1015 King George Blvd.,
Apt 702, Savannah, Georgia 31419 (US).



(74) Agent: DORITY & MANNING; 55 Beattie Place, Suite
1600, Greenville, SC 29601 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: THIN-LAYER POROUS OPTICAL SENSORS FOR GASES AND OTHER FLUIDS



(57) Abstract: A gas sensor uses optical interferents in a porous thin film cell to measure the refractive index of the pore medium. As the medium within the pores changes, spectral variations can be detected. For example, as the pores are filled with a solution, the characteristic peaks exhibit a spectral shift in one direction. Conversely, when tiny amounts of gas are produced, the peaks shift in the opposite direction. This can be used to measure gas evolution, humidity and for applications for other interferometric-based sensing devices.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*